

Maximize your time on the job with products specifically designed for high performance cutting, grinding and cleaning stainless steel.



WORKING WITH STAINLESS STEEL

Stainless steel is more resistant to the elements than carbon steel, which makes it more desirable — and more expensive, so it is critical to choose the right abrasives and brushes. Doing so can significantly improve production efficiency, lower rework costs and reduce material waste.

CROSS-CONTAMINATION

Although stainless steels are chosen for their corrosion resistance, they are not immune to it. Many companies utilize both carbon and stainless steel in their manufacturing operations, and one of the biggest concerns is the potential for cross-contamination. The surface is what gives stainless steel its corrosion resistance so it's important to properly protect it. This includes avoiding any mechanical damage, such as scratches during fabrication, that can cause passive film deterioration.

Stainless steel can become contaminated in many ways, the most frequent is by exposure to iron while using the wrong cleaning or grinding product. For example, cleaning or finishing with a carbon steel brush on stainless steel may leave a residue on the surface of the workpiece and lead to "after rust". Weiler's stainless steel wire brushes are manufactured using wire drawn from type 302 stainless steel. Although 302 stainless is typically a non-magnetic material, it is important to remember that the amount of cold working that it experiences during the wire-drawing process causes the wire to become magnetic. For this reason, proper storage and handling of stainless steel brushes are critical to prevent crosscontamination and "after rust" issues.

NEW COLOR-CODED BRUSHES

Our popular stainless steel brushes are now color-coded black for easy identification, even during operation.

Cross-contamination is avoidable. Marking products to distinguish them can be valuable, as can splitting operation areas in the manufacturing facility between carbon and stainless. Limiting operator access to storage areas can also help. Remember to always avoid storing a carbon brush next to a stainless steel brush where they could come into contact with each other.

Cross-contamination of abrasives and brushes can cause "after rust" on expensive stainless steel parts. Never use these products on stainless steel after exposing them to carbon steel or other metals.

HEAT DISCOLORATION

When cutting, grinding or finishing stainless steel, heat discoloration is a potential issue that can arise if an operator builds up too much heat. Heat discoloration in the metal almost resembles an "oil spill". When this happens, the heat discoloration must be finished out of the stainless steel, requiring an extra step that costs both time and money. To help mitigate this problem, there are abrasive grains and coatings that allow operators to either use less pressure, reduce surface friction or both. Abrasives should always be changed before they are completely worn out, as they will generate more heat at the end of their lives.







PRODUCT SELECTION

When working with stainless steel look for specific product features that will increase productivity and lower total cost of use.

Choosing the right product increases operator efficiency, reduces rework, improves finish, and eliminates the risk of cross-contamination.



BONDED ABRASIVES

Look for contaminant-free or **INOX** markings on cutting and grinding wheels. This means they are manufactured with additives that contain less than 0.1% iron, sulfur & chlorine



COATED ABRASIVES

WEILER

TIGER

Always choose a product marked as contaminant-free to avoid contamination of the workpiece.

Top coated products are often used on stainless steel because they grind cooler, eliminating loading and heat buildup.

NON-WOVEN ABRASIVES

Non-woven abrasive products can be used in a broad range of stainless steel surface conditioning applications, from cleaning and finishing, to deburring and light blending.

WIRE BRUSHES

Type 302 stainless wire is used in the manufacturing of brushes for its relative durability and aggressive action as well as its austenitic properties that ensure corrosion resistance.

Type 316 stainless wire brushes are used for applications requiring extreme corrosion protection. (see product listing for details)

Degreased brushes are used for applications where all residue must be eliminated.

Type 316 stainless brushes and degreased brushes are available by special order. Longer lead times and minimum order quantities apply. Contact your Weiler representative for details.

STAINLESS STEEL TYPES

The two most common grades of stainless steel used in the industrial market are 304 and 316. Both have a high percentage of chromium, which forms the protective barrier that gives stainless steel its name. However, 316 is more resistant to chlorides (sea water, salts) due to the addition of molybdenum. It also costs significantly more than 304, so it is primarily used in more niche applications where the value of it can be realized.

AUSTENTIC

Non-magnetic

Excellent Corrosion Resistance

Magnetic

FERRITIC

USES: Automotive exhaust systems

MARTENSITIC

Limited Corrosion Resistance

Magnetic

USES: Cutlery, multi-purpose tools

DUPLEX

Very Good Corrosion Resistance

Magnetic

USES: Heat exchangers, condensers, pressure vessels, piping systems

USES Automotive trim, cookware, processing equipment

Good Corrosion Resistance

CUTTING & GRINDING

Weiler's contaminant-free cutting, grinding and combination wheels help metal fabrication professionals get demanding stainless steel jobs done right and done fast.



MAX PERFORMANCE SUPERIOR LIFE & CUT



HIGH PERFORMANCE LONG LIFE & FAST CUT



CUT RATE: • • • • •

TIGER CERAMIC Self-sharpening, cool cutting Tiger Ceramic grinds at lower temperatures with less friction and less effort, reducing heat discoloration of the workpiece.



TIGER INOX Tiger INOX wheels deliver a worry-free solution for stainless steel applications.





GRAIN TYPE White aluminum oxide





(Hard-to-grind metals include tool steel, inconel, high nickel alloy, titanium and armored steel)

BEST ON STAINLESS

(and harder grade steel)



58131



UltraCut 1mm cutting wheels deliver lightning fast, super smooth, clean cuts on sheet metal, tubes, profiles, and small cross-section rods.

4-1/2" 1 mm INOX60T 13,300 50 58130	1833	J. J		s / Contaminant-free		
		4-1/2" 1 mm	INOX60T	13,300	50	58130
5" 1 mm INOX60T 12,200 50 58131	1000	5" 1 mm	INOX60T	12,200	50	58131



Weiler's cutting wheels provide a consistent, well balanced, high quality solution. A smooth outer layer reduces friction for an effortless cut and less kickback.

	RAMIC CU & Cut / Contami		EELS		PE 1 Arbor		PE 1 Arbor
Dia.	Thickness	Grade	Max. RPM	Pack	Item #	Pack	Item #
3"	1/16"	CER36T	25,000	100	58345	100	58342
4"	1/16"	CER36T	19,000	25	58351	25	58348





Weiler's cutting wheels provide a consistent, well balanced, high quality solution. A smooth outer layer reduces friction for an effortless cut and less kickback. $\int_{S0^{\circ}}$

TIGER C	ERAMIC	CUTTIN	G WHEE	TYF LS 7/8 " /	PE 1 Arbor	TYP 7/8'' /		TYPI 5/8''-1 '	
Superior Life	& Cut / Co	ntaminant-fr	ee*						
Diameter	Thickness	Grade	Max. RPM	Std. Pack	Item #	Std. Pack	Item #	Std. Pack	Item #
4-1/2"	.045"	CER60S	13,300	25	58300	25	58305	10	58306
5"	.045"	CER60S	12,200	25	58301	25	58307	10	58308
6"	.045"	CER60S	10,200	25	58302	25	58309	10	58310
7"	.060"	CER60S	8,500	25	58303	25	58311	10	58312
TIGER INOX CUTTING WHEELS TYPE 1 7/8" Arbor TYPE 27 7/8" Arbor TYPE 27 5/8"-11 Hub Long Life & Fast Cut / Contaminant-free* Image: Contaminant-free Image: Contaminant-free									
Diameter	Thickness	Grade	Max. RPM	Std. Pack	ltem #	Std. Pack	Item #	Std. Pack	Item #
4-1/2"	.045"	INOX60S	13,300	25	58100	25	58110	10	58109

58101

58102

58103

25

25

25





.045'

.045'

.060

INOX60S

INOX60S

INOX60S

12,200

10,200

8,500

5"

6"

Tiger type 27 grinding wheels are designed with fiberglass cut back from the edge to provide instant aggressive grinding on new wheels.

25

25

25

58111

58112

58107

10

58113

7

ר<u>ן</u> 190°

TYPE 27

5/8"-11 Hub

	TIGER CERAMIC Superior Life & Cut / Contaminant-free*			TYPE 27 5/8" Arbor		TYPE 27 7/8" Arbor		27 1 Hub	
Dia.	Thickness	Grade	Max. RPM	Std. Pack	Item #	Std. Pack	Item #	Std. Pack	Item #
4"	1/4"	CER24R	15,300	10	58335		—		
4-1/2"	1/4"	CER24R	13,300	—	—	10	58325	10	58326
5"	1/4"	CER24R	12,200	—		10	58327	10	58328
6"	1/4"	CER24R	10,200	—		10	58329	10	58330
7"	1/4"	CER24R	8,500	—	—	10	58331	10	58332
9"	1/4"	CER24R	6,600	—	—	10	58333	10	58334
TIGER INOX GRINDING WHEELS				TYPE 27 5/8" Arbor		TYPE 27 7/8" Arbor		E 27 1 Hub	

TIGER INOX GRINDING WHEELS

Long Life & Fast Cut / Contaminant-free*

Long En		, oontaniin							
Dia.	Thickness	Grade	Max. RPM	Std. Pack	Item #	Std. Pack	Item #	Std. Pack	Item #
4-1/2"	1/4"	INOX24R	13,300	—	—	10	58121	10	58120
5"	1/4"	INOX24R	12,200	—	—	10	58123	10	58122
7"	1/4"	INOX24R	8,500	—	—	10	58125	10	58124
9"	1/4"	INOX24R	6,600	—	—	10	58127	10	58126



TYPE 27 COMBO WHEELS

Weiler's cut and grind combination wheels offer flexibility and efficiency 0-45° when switching between cutting and grinding applications.

TYPE 27

7/8" Arbor

IGER CERAMIC COMBO WHEELS uperior Life & Cut / Contaminant-free*					E 27 Arbor	TYPE 27 5/8"-11 Hub		
Diameter	Thickness	Grade	Max. RPM	Std. Pack	Item #	Std. Pack	Item #	
4-1/2"	1/8"	CER30T	13,300	25	58315	10	58316	
5"	1/8"	CER30T	12,200	25	58317	10	58318	
6"	1/8"	CER30T	10,200	25	58319	10	58320	
7"	1/8"	CER30T	8,500	25	58321	10	58322	
9"	1/8"	CER30T	6,600	25	58323	10	58324	

TIGER INOX COMBO WHEELS

Long Life & Fast Cut / Contaminant-free*

0							
Diameter	Thickness	Grade	Max. RPM	Std. Pack	Item #	Std. Pack	Item #
4-1/2"	1/8"	INOX30T	13,300	25	58115	10	58114
7"	1/8"	INOX30T	8,500	25	58117	10	58116
9"	1/8"	INOX30T	6,600	25	58119	10	58118



CUTTING TIPS

- A higher cutting force is needed for stainless steel.
- The thinner the cut, the faster the cut and less material that must be removed.
- Utilize a slight sawing motion with minimal depth of cut will help maximize wheel life and cut efficiency.

GRINDING & FINISHING

Weiler's Abrasive Flap Discs grind and finish in one step, saving you time and money. There's no switching from a Type 27 grinding wheel to a resin fiber disc.



MAX PERFORMANCE CUT RATE: • • • • • LIFE: • • • • • **SUPERIOR LIFE & CUT** TIGER CERAMIC **GRAIN TYPE BEST ON** STEEL / METAL ALUMI TOP COAT for cool, fast grinding Ceramic alumina protects from heat discoloration and STAINLESS HARD-TO-GRIND prevents loading on soft alloys **CONTAMINANT-FREE** (Hard-to-grind metals include CONTAIN LESS THAN 0.1% IRON, SULFUR & CHLORINE tool steel, inconel, high nickel alloy, titanium and armored steel) **HIGH PERFORMANCE** CUT RATE: • • • • • LIFE: • • • • • **LONG LIFE & FAST CUT** TIGER X IGER) **GRAIN TYPE BEST ON** • FLAT SURFACE GRINDING Ceramic & zirconia alumina STEEL / METAL • Less effort required STAINLESS **CONTAMINANT-FREE** • Fast grinding & long life CONTAIN LESS THAN 0.1% IRON. SULFUR & CHLORINE

STANDARD DENSITY FLAP DISCS

Diger Ceram op Coated for Cool C		Back	TYPE 29 7/8" Arbor	TYPE 29 5/8"-11 Hut	
Diameter	Grit	Max. RPM	Std. Pack	Item #	Item #
4-1/2"	36	13,000	10	50100	50104*
	40			50101	50105*
	60			50102	50106*
	80			50103	50107*
7"	36	8,600	10	50108	50112*
	40			50109	50113*
	60			50110	50114*
	80			50111	50115*





TIGER X

	ng & Lor	ng Life on Flat Alumina / F		TYPE 29 7/8" Arbor	TYPE 29 5/8"-11 Hub	TYPE 27 7/8" Arbor	TYPE 27 5/8"-11 Hub
Diameter	Grit	Max. RPM	Std. Pack	Item #	Item #	Item #	ltem #
4-1/2"	36	13,000	10	51200	51204*	-	_
	40			51201	51205*	51223	51226*
	60			51202	51206*	51224	51227*
	80			51203	51207*	51225	51228*
5"	36	12,000	10	51208	-	-	-
	40			51209	51212*	-	-
	60			51210	51213*	-	_
	80			51211	51214*	-	_
6″	40	10,200	10	51237	51241	-	-
	60			51238	51242	-	_
	80			51239 •	51243 •	-	_
7"	36	8,600	10	51215	51219*	-	-
	40			51216	51220*	51229	51232*
	60			51217	51221*	51230	51233*
	80			51218	51222*	51231	51234*

GRINDING TIPS

When grinding stainless, using a very coarse grit (36 grit) increases the risk of gouging the material. 60 or 80 grit is a good starting point for many applications. Always start grinding with a pullback motion instead of a push to reduce the chance of gouging this expensive material.

STYLE

CONICAL (Type 29)

15° – 35°



The angled flaps maximize surface contact for aggressive stock removal on flat surfaces.



Smooth grinding, blending and finishing on flat surfaces and slight contours.

HIGH DENSITY (Type 27) 0° – 15°



TYPE 27

7/8" Arbor

TYPE 27

5/8"-11 Hub

Conformable to irregular surfaces. Smooth grinding, blending and finishing on flat surfaces.

ANGLED (Type 27 / Hybrid) 0° – 35°

Curved flaps for grinding fillet welds, T-joints, and hard-to-reach areas.

HIGH DENSITY FLAP DISCS

High density flap discs last up to 40% longer than standard density discs and are more conformable to irregular surfaces. High density flap discs offer smooth grinding, blending and finishing on flat surfaces.

TIGER CERAMIC HD (SABER TOOTH)

Top Coated for Cool Grinding on Irregular Surfaces / Ceramic Alumina / Phenolic Back

Diameter	Grit	Max. RPM	Std. Pack	Item #	Item #
4-1/2"	40	13,000	10	50130	50133*
	60			50131	50134*
	80			50132	50135*
7"	40	8,600	10	50136	50139*
	60			50137	50140*
	80			50138	50141*



ANGLED FLAP DISCS

The 90° angled flap design is ideal for grinding fillet welds, T-joints and other hard-to-reach places. The flaps wrap around the edge of the backing plate, optimizing flap-to-metal contact and providing exceptional feel and control while grinding.

TIGER CERAMIC ANGLED

Coated for Cool G	rinding on Fillet Wel	ds / Ceramic Alumi	na / Phenolic Back	7/8" Arbor	5/8"-11 Hub
Diameter	Grit	Max. RPM	Std. Pack	Item #	Item #
4-1/2"	40	13,000	10	51312	51315
	60			51313	51316
	80			51314	51317
5"	40	12,000	10	51318	51321
	60			51319	51322
	80			51320	51323



TRIMMABLE FLAP DISCS

A trimmable backing plate allows the operator to increase the flap overhang. This feature provides the versatility to adjust for hard-to-reach areas such as fillet welds and irregular shapes.

TIGER CERAM Top Coated for Cool (e Composite Back	TYPE 29 7/8" Arbor	TYPE 29 5/8"-11 Hub	
Diameter	Grit	Max. RPM	Std. Pack	Item #	Item #
4-1/2"	40	13,000	10	50117	50121*
	60			50118	50122*
	80			50119	50123*



GRINDING, BLENDING & FINISHING

Weiler's coated abrasive resin fiber & blending discs are designed to help get the most demanding stainless steel jobs done right and done fast.



MAX PERFORMANCE SUPERIOR LIFE & CUT



HIGH PERFORMANCE LONG LIFE & FAST CUT



CUT RATE: • •

TIGER CERAMIC TOP COAT for cool, fast grinding protects from heat discoloration and prevents loading on soft alloys

TIGER ZIRC **INFUSED WITH CERAMIC** for faster grinding and longer life. Disc design optimizes grain shedding and promotes cool grinding on stainless

GRAIN TYPE Ceramic alumina

CONTAMINANT-FREE CONTAIN LESS THAN 0.1% IRON, SULFUR & CHLORINE

GRAIN TYPE Ceramic & zirconia alumina

CONTAMINANT-FREE CONTAIN LESS THAN 0.1% IRON, SULFUR & CHLORINE




BEST ON STEEL / METAL



RESIN FIBER DISCS

With premium grain mixes that aggressively remove metal and a superior design that locks the grain in, Tiger RFD's are designed to deliver serious grinding solutions. All sizes are available in a standard arbor or quick change hub to reduce down time and eliminate interference from adapter rings.





TIGER CERAMIC RESIN FIBER DISCS / Ceramic Alumina / Superior Life & Cut Rate on Metal

Diameter	Grit Size	Standard Pack	7/8" Arbor Item #	5/8"-11 Hub Item #
4-1/2"	24	25	69850	69880
	36		69851	69881
	50		69852	69882
	60		69853	69883
	80		69854	69884
5"	24	25	69857	69887
	36		69858	69888
	50		69859	69889
	60		69860	69890
	80		69861	69891
7"	24	25	69864	69894
	36		69865	69895
	50		69866	69896
	60		69867	69897
	80		69868	69898
9"	24	25	69871	69901
	36		69872	69902
	50		69873	69903
	60		69874	69904
	80		69875	69905
Do not exceed maximum RPM of	back-up pad.			

TIGER ZIRC RESIN FIBER DISCS / Zirconia Alumina / Ceramic Infused for Faster, Longer Grinding

Diameter	Grit Size	Standard Pack	7/8" Arbor Item #	5/8"-11 Hub Item #
4-1/2"	24	25	59731	59931
	36		59732	59932
	50		59733	59933
	60		59734	59934
	80		59735	59935
	100		59736	59936
	120		59737	59937
5"	24	25	59701	59901
	36		59702	59902
	50		59703	59903
	60		59704	59904
	80		59705	59905
	100		59706	59906
	120		59707	59907
7"	24	25	59711	59911
	36		59712	59912
	50		59713	59913
	60		59714	59914
	80		59715	59915
	100		59716	59916
	120		59717	59917
Do not exceed maximum RPM of	back-up pad.			

Max. RPM

11,000

10,000

8,500

6,500

Standard Pack

1

1

Item #

59611

59600

59601

59602

59603

59604

A.







BLENDING DISCS

* Other thread sizes available on special orders.

Description

4-1/2" Back-up Pad

5" Back-up Pad

7" Back-up Pad

9" Back-up Pad

Spanner Wrench

Disc Nut

ACCESSORIES FOR RESIN FIBER DISCS

Thread Size

5/8"-11*

5/8"-11*

5/8"-11

5/8"-11

5/8"-11

Weiler's cloth backed coated abrasive blending discs are for use on right angle air tools. Available with either a metal hub or a plastic button fastening system, the flexible back-up pads give the discs a great deal of conformability.

TIGER CERAMIC BLENDING DISCS / Ceramic Alumina / Superior Life & Cut Rate on Metal

Ideal for a wide range of light fabrication, repair and maintenance applications.

			lter	m# 🗳
Diameter	Grit Size	Standard Pack	Type S Hub Style	Type R Hub Style
2"	36	100	60150	60170
	60		60151	60171
	80		60152	60172
3"	36	50	60155	60175
	60		60156	60176
	80		60157	60177



60150





BACK-UP PADS FOR BLENDING DISCS / 1/4" Stem

BACK-UP PADS FUR BLENDING D		JISUS / 1/4" Stem		m# 🕙
Diameter	Grit Size	Standard Pack	Type S Hub Style	Type R Hub Style
2"	25,000	1	51551	60508
3"	20,000	1	51552	60509

Do not exceed maximum RPM of back-up pad. *Compatible with 3M Roloc™ back-up pads. (Roloc™ is a trademark of 3M.)


+Compatible with Norton Speed-Lok® TS back-up pads. (Speed-Lok® TS is a registered trademark of Norton Co.)



FINISHING

Weiler's non-woven abrasive products produce scratch patterns that can be compared to those produced by coated abrasive products. However, their pliable nature results in a softer, less pronounced scratch-line pattern. The strength of these products is producing decorative finishes ranging from satin to near-mirror polish.

Denser non-woven products are suitable for applications requiring light stock removal such as removing large, well-attached burrs and blending minor tool marks and imperfections.



All non-woven products are fabricated from base materials that are composed of a random "web" of nylon fibers that have been bonded together with synthetic resins and impregnated with abrasive grains. Although these materials vary in fiber density, their three dimensional nature results in specialty abrasive products that are pliable,

conformable to the work surface, and limited in their ability to remove base stock.

Non-woven products resist loading and perform consistently as new, fresh abrasive grains are exposed as the nylon fibers wear away from the product during use. Non-woven abrasives can be used either wet or dry on a range of materials including stainless steel. Non-woven products are designed for use where stock removal is not required. Non-wovens begin where coated abrasives leave off.

Grade	Grit Range
Ultra Fine	600
Very Fine	240-360
Fine	180-220
Medium	100-150
Coarse	50-80

51460

HAND PADS

HAND PADS - For cleaning and conditioning surfaces by hand. Unlike steel wool, hand pads are non-metallic, and do not produce "after-rust" on work surfaces. Hand pads can be used in wet applications.

Size	Grain	Grade	Description	Standard Pack	Item Number
	-		Industrial Grade	,	
6" x 9"	Silicon Carbide	Ultra Fine	Finishing (Grey)	60	51434
6" x 9"	Aluminum Oxide	Medium	Economy General Purpose (Maroon)	60	51460
6" x 9"	Aluminum Oxide	Med/ Coarse	General Purpose (Maroon)	60	51444
6" x 9"	Aluminum Oxide	Heavy-Duty	Heavy-Duty (Tan)	40	51454
			Commercial Grade		
6" x 9"	Aluminum Oxide	Fine	Economy (Green)	400	51456
6" x 9"	Aluminum Oxide	Medium	Standard-Duty (Green)	60	51457
6" x 9"	Aluminum Oxide	Heavy-Duty	Heavy-Duty (Green)	60	51458
			20% thicker than Standard Duty		

SURFACE CONDITIONING DISCS

Surface conditioning discs have an open construction, scrim reinforcement and a superior resin system. These features minimize loading, heat buildup, fraying of disc edges, grain shedding and extend disc life, providing superior performance.

TYPE R HUB STYLE DISCS - General Purpose

Compatible with 3M Roloc[™] back-up pads.

Diameter	Grade	Standard Pack	Item Number
2"	Very Fine (Blue)	50	51530
	Medium (Maroon)		51531
	Coarse (Brown)		51532
3"	Very Fine (Blue)	25	51533
	Medium (Maroon)		51534
	Coarse (Brown)		51535



BACK-UP PADS FOR SURFACE CONDITIONING DISCS / 1/4" Stem

			Item Number
Diameter	Grit Size	Standard Pack	Type R Hub Style
2"	25,000	1	60508
3"	20,000	1	60509



Do not exceed maximum RPM of back-up pad.

*Compatible with 3M Roloc[™] back-up pads. (Roloc[™] is a trademark of 3M.)

+Compatible with Norton Speed-Lok® TS back-up pads. (Speed-Lok® TS is a registered trademark of Norton Co.)

& LOOP STYL	E DISCS		
Diameter	Grade	Standard Pack	Item Number
3"	Very Fine (Blue)	25	51506
	Medium (Maroon)		51507
	Coarse (Brown)		51508
4-1/2"	Very Fine (Blue)	10	51512
	Medium (Maroon)		51513
	Coarse (Brown)		51514
5"	Very Fine (Blue)	10	51515
	Medium (Maroon)		51516
	Coarse (Brown)		51517
7"	Very Fine (Blue)	10	51521
	Medium (Maroon)		51522
	Coarse (Brown)		51523



51533



HOOK & LOOP STYLE BACK-UP PADS

Diameter	Arbor Hole or Stem Size	Max. RPM	Standard Pack	ltem Number
3"	1/4" Stem	18,000	1	51562
4-1/2"	5/8" -11 Arbor	13,000	1	51569
5"	5/8" -11 Arbor	10,000	1	51575
7"	5/8" -11 Arbor	6,000	1	51578



ACCESSORIES FOR BRUSHES & ABRASIVES



56494

ADAPTING NUTS & SPANNER WRENCH For 4-1/2" - 9" Angle Grinders.

	Description	Adapts To	Min. Wheel Thickness	Standard Pack	Item Number
_	Adapting Nuts	5/8" to 3/8"-24	1/16"	1	56484
_	Adapting Nuts	7/8" to 5/8"-11	1/16"	1	56494
_	Spanner Wrench	-	-	1	56495





DRIVE ARBORS for mounting small diameter wheels into a collet or chuck.



07724







Arbor Dia.	Stem Dia.	Stem Length	Length of Shaft	For Brushes with a Max. Dia. of nthreaded Sha	Overall Length	Max. RPM	Standard Pack	ltem Number
1/4"	1/4"	1-1/8"	3/16"	2"	2-1/16"	20.000	5	07723
3/8"	1/4"	1-1/8"	3/16"	4"	1-15/16"	20,000	5	07722
	1			Threaded Shaf	t			
1/4"	1/4"	1-1/16"	1-1/8"	2"	2-9/16"	20,000	5	07725
3/8"	1/4"	3/4"	3/4"	3"	1-9/16"	25,000	5	07727
3/8"	1/4"	1"	1-1/8"	3"	2-9/16"	20,000	5	07726
1/2"	1/4"	3/4"	3/4"	3"	1-3/4"	25,000	5	07724
1/2"	1/4"	7/8"	3/4"	3"	1-11/16"	20,000	5	07721
5/8"	1/4"	3/4"	3/4"	3"	1-13/16"	25,000	5	07729

PLASTIC ADAPTERS for mounting small diameter wheels onto various arbor sizes.

Fixed Arbor Hole Size	Adapted Arbor Hole Size	Standard Pack	Item Number
3/8"	1/4"	10	04403
1/2"	1/4"	10	04400
1/2"	3/8"	10	04401
5/8"	1/2"	10	04402



04402

METAL ADAPTERS for Medium & Wide Face Brushes. Used in pairs & priced per pair.

For Brush Arbor Hole Size	Adapted Arbor Hole Size	Item Number
2"	1/2"	03809
	5/8"	03810
	3/4"	03811
	7/8"	03824
	1"	03812
	1-1/4"	03813
	1-1/2"	03814

302 & 316 STAINLESS STEEL WIRE

Weiler's stainless steel wire brushes are manufactured using wire drawn from **TYPE 302** stainless steel. Although 302 stainless is typically a non-magnetic material, it is important to remember that the amount of cold-working that it experiences during the wire-drawing process causes it to become magnetic. For this reason, proper storage and handling of stainless steel brushes is critical to prevent cross-contamination and "after rust" issues.

Type 302 is widely used in the manufacturing of power brushes for its relative durability and aggressive action as well as for its austenitic properties that insure the corrosion resistance of the materials on which it is applied. Brushes with **TYPE 316** wire are available for applications requiring extreme corrosion protection.

DEGREASED BRUSHES

Degreased brushes are used for applications where all residue must be eliminated. During the manufacturing process oil comes in contact with the stainless steel wire. If there is excess oil it can be spun off of the brush and cause oil stains or "splatter" stains on stainless steel or aluminum workpieces. These stains can be undesirable and an extra degreasing process may be needed to eliminate the "splatter" stains.


ORDERING INFO

Type **316 stainless brushes** and **degreased brushes** are available by special order. Longer lead times and minimum order quantities apply. Contact your Weiler representative for details.

WELD CLEANING BRUSHES

Weiler's stringer bead wheels are the most effective weld cleaning tools for the most demanding users. Our premium weld cleaning brushes are manufactured to the most stringent quality standards, utilizing the highest quality wire available. The twist puts all the sharp tips at the end of the knots, making them the fastest, most aggressive weld cleaning tools on the market.





13138



ROUGHNECK. MAX



Roughneck Max wheels have been re-engineered to MAXimize life, efficiency and consistency. But that is only a small part of what makes this brush better...

- Smooth & Responsive Improved feel and comfort during use makes brush operation effortless
- No Long Wire Breakage Stronger, sharper wire delivers consistency and performance you can count on
- Cleans 40% Faster Unmatched cleaning power compared to competitors
- Less Force Required The operator can apply less pressure to clean, letting the wire do the work

ROUGHNECK MAX STRINGER BEAD WHEEL / 302 Stainless

Delivers unmatched weld cleaning performance by maximizing life, efficiency and consistency.

The 4	brusnes are	recommended to	or cleaning	root pass	weids, surr	race prep and i	other cleaning	applications.
		1	1	1	1	1	1	1

Dia.	Wire Size	Arbor Hole	No. of Knots	Face Width	Trim Length	Thickness at Face Plates	Max. RPM	Std. Pack	ltem Number	
4"	.020	5/8"-11 UNC	32	3/16"	7/8"	7/16"	20,000	5	13138	
	.020		02	0,10	1 110	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	20,000	1 0		-

BOLD BLACK ITEM numbers indicate color-coded brushes for easy identification.

Indicates wire brush items available in 316 STAINLESS STEEL

ROUGHNECK



ROUGHNECK STRINGER BEAD WHEELS / 302 Stainless / The standard for high-performance weld cleaning brushes. Narrow face brushes are suitable for cleaning root and hot passes and reaching into corners; wider face wheels can be used for cleaning filler and cap passes as well as for other surface prep and cleaning applications.

Dia.	Wire Size	Arbor Hole	No. of Knots	Face Width	Trim Length	Thickness at Face Plates	Max. RPM	Std. Pack	ltem Number
		,		Root Pa	ss Brushes				
4"	.020	1/2"-3/8"	32	3/16"	7/8"	7/16"	20,000	10	08954 🗨
		M10 x 1.25						5	13132 🗨
		M14 x 2.0						5	13134 🗨
		3/8"-24 UNF						5	13135 🗨
		1/2"-13 UNC						5	13137 🗨
4-1/2"	.020	5/8"-11 UNC	38	3/16"	13/16"	3/8"	15,000	5	13238
		7/8"						5	13249 🗨
5"	.020	5/8"-11 UNC	38	3/16"	7/8"	3/8"	12,500	5	08806
6"	.020	5/8"-11 UNC	48	3/16"	1-3/8"	3/8"	12,500	5	08786†
			56		1-1/8"	7/16"		10	09500
7"	.020	5/8"-11 UNC	56	3/16"	1-1/8"	7/16"	9,000	10	09200
				Filler Pa	ss Brushes				
6"	.023	5/8"-11 UNC	24	1/2"	1-3/8"	9/16"	12,500	5	08796
		5/8"-11 UNC	30	1/2"	1-1/4"	5/8"		5	08926
		5/8"-11 UNC	30	5/16"	1-3/8"	1/2"		5	09396
† Light Duty							tomo oro olao ovoi	labla in 216 ST	

Items are also available in 316 STAINLESS STEEL

THE DUALLY®



- Maximum Cleaning Action Featuring a knot twist with the most aggressive cutting action, the new dual-hex
 nut makes it easier for the user to regularly switch mounting position and keep the brush running at peak performance.
- **Long Wheel Life** Utilizing the highest quality heat-treated Steel wire and construction that virtually eliminates knot movement, the Dually delivers smooth operation and long life for the lowest cleaning costs in demanding multi-pass welding applications such as pipeline construction.
- **Improved User Safety** The one-piece, dual-hex nut is designed to provide adequate tool clearance so there is no need to remove the guard from the grinder in order to change the position of the wheel.



Removing weld slag before the next weld pass.

DUALLY STRINGER BEAD WHEELS / **302 Stainless** / Feature a dual-hex nut design that simplifies periodic flipping of the wheel for maximum cleaning action, long life, and safer use.

Dia.	Wire Size	Arbor Hole	No. of Knots	Face Width	Trim Length	Thickness at Face Plates	Max. RPM	Standard Pack	ltem Number
				Root Pas	s Brushes				
4-1/2"	.020	5/8"-11 UNC	38	3/16"	13/16"	3/8"	15,000	5	79811
5"	.020	5/8"-11 UNC	38	3/16"	7/8"	3/8"	12,500	5	79812
6"	.020	5/8"-11 UNC	56	3/16"	1-1/8"	7/16"	12,500	5	79815
7"	.020	5/8"-11 UNC	56	3/16"	1-1/8"	7/16"	9,000	5	79810
· · · · · · · · · · · · · · · · · · ·				Filler Pas	s Brushes				
5"	.023	5/8"-11 UNC	24	1/2"	7/8"	3/8"	12,500	5	79813
6"	.023	5/8"-11 UNC	30	1/2"	1-1/4"	5/8"	12,500	5	79814

Items are also available in 316 STAINLESS STEEL







Previously known as Vortec Pro^{*}, Wolverine wheels offer professional grade quality and performance at a great value. Re-engineered, these 32 knot wheels deliver 20% MORE life while maintaining aggressive cleaning power for weld cleaning applications.

WOLVERINE STRINGER BEAD WHEEL / **302 Stainless** / Upgraded to 32 knots to deliver 20% longer life. These wheels are manufactured using similar product construction and same exacting standards as other Weiler weld cleaning brushes; they have been engineered for cost-effective use in less demanding cleaning applications.

Dia.	Wire Size	Arbor Hole	No. of Knots	Face Width	Trim Length	Thickness at Face Plates	Max. RPM	Standard Pack	ltem Number
4"	.020	5/8"-11 UNC	32	3/16"	7/8"	7/16"	20,000	5	36219

BOLD BLACK ITEM numbers indicate color-coded brushes for easy identification.

WOLVERINE STRINGER BEAD WHEELS / 302 Stainless / Manufactured using similar product construction and to the same exacting standards as other Weiler weld cleaning brushes; they have been engineered for cost-effective use in less demanding applications.

Dia.	Wire Size	Wire Type	Arbor Hole	No. of Knots	Face Width	Trim Length	Max. RPM	ltem Number
5"	.020	Stainless	5/8"-11 UNC	38	3/16"	7/8"	12,500	36296





CLEANING

Weiler's superior construction, highest quality materials, state of the art manufacturing and exacting quality standards deliver the most consistent brush performance. Each brush is designed to provide the best performance at the lowest cost-of-use.





08264

08325	





13466





STANDARD TWIST WHEELS / 302 Stainless / Heavy-duty brushing action	
with some flexibility; ideal for demanding cleaning applications on somewhat irregular surfaces.	

	'		0	0 11			0		-	
Dia.	Wire Size	Arbor Hole	No. of Knots	Face Width	Trim Length	Max. AH Avail.	Thickness at Face Plates	Max. RPM	Std. Pack	ltem Number
3"	.0118	1/2"-3/8"	20	3/8"	5/8"	1/2"	7/16"	25,000	10	08254
	.014	1/2"-3/8"				1/2"	7/16"		10	08264
	.014	3/8"-24 UNF				_	_		5	13208
	.020	1/2"-3/8"				1/2"	7/16"		10	08274
4"	.0118	1/2"-3/8"	24	1/2"	7/8"	1/2"	7/16"	20,000	10	08284
	.014	1/2"-3/8"				1/2"	7/16"		10	08294
	.014	M10 x 1.25				_			5	13107
	.014	M10 x 1.50				-	-		5	13108
	.014	M14 x 2.0				_			5	13109
	.014	3/8"-24 UNF				_			5	13110
	.014	5/8"-11 UNC				_			5	13113
	.020	1/2"-3/8"				1/2"	7/16"		10	08314
6"	.0118	5/8"-1/2"	24	1/2"	1-3/8"	1-1/4"	9/16"	9,000	10	08325
	.016	5/8"-1/2"				1-1/4"	9/16"		10	08345
	.016	5/8"-11 UNC							2	08346
8"	.0118	5/8"	38	5/8"	1-5/8"	2"	1/2"	6,000	2	08375
	.016	5/8"				-	_		2	08395

BOLD BLACK ITEM numbers indicate color-coded brushes for easy identification.

WOLVERINE[™] STANDARD TWIST WHEELS / 302 Stainless

Aggressive brushing action for general-purpose surface cleaning applications.

Dia.	Wire Size	Arbor Hole	No. of Knots	Face Width	Trim Length	Max. AH Avail.	Thickness at Face Plates	Max. RPM	Std. Pack	ltem Number
4"	.014	5/8"-11 UNC 1/2"-3/8"	20 24	1/2" 5/8"	7/8" 7/8"	1/2"	 9/16"	20,000 20,000	5 10	36213 36293

STANDARD TWIST BEVEL BRUSHES / 302 Stainless / Saucer-shaped radial wheels that provide a heavy-duty brushing action with some flexibility; ideal for cleaning fillet welds and into corners.

rovide a heav	/y-duty brushi	ng action with	some flexibilit	y; ideal for cle	aning fillet we	lds and into co	orners.	
Diameter	Wire Size	Arbor Hole	No. of Knots	Face Width	Trim Length	Max. RPM	Std. Pack	ltem Number
4"	.014	5/8"-11 UNC	20	3/8"	3/4"	12,500	1	13416
4"	.020	5/8"-11 UNC	20	3/8"	3/4"	12,500	1	13436
4-1/2"	.014	5/8"-11 UNC	20	3/8"	1"	12,500	1	13466
4-1/2"	020	5/8"-11 UNC	20	3/8"	1"	12 500	1	13486

STANDARD TWIST WHEELS / **302 Stainless** / 1/4" Stem / Heavy-duty brushing action with some flexibility; ideal for deburring and demanding cleaning applications on somewhat irregular surfaces.

Diameter	Wire Size	No. of Knots	Face Width	Trim Length	Max. RPM	Standard Pack	ltem Number
3-1/4"	.014	20	3/8"	5/8"	25,000	5	17684
4"	.014	24	1/2"	7/8"	20,000	5	17691

CABLE TWIST WHEELS / 302 Stainless / Maximum brushing action with minimal flexibility ideal for demanding cleaning and coating removal applications on relatively smooth surfaces.

Dia.	Wire Size	Arbor Hole	No. of Knots	Face Width	Trim Length	Max. AH Avail.	Thickness at Face Plates	Max. RPM	Std. Pack	ltem Number	
4"	020	M10 x 1.50	24	1/4"	7/8"	_	_	20,000	5	13272	
		5/8"-11 UNC				_	_			13276	
6"	.023	5/8"-1/2"	24	3/8"	1-3/8"	1-1/4"	9/16"	9,000	2	08695	

Items are also available in 316 STAINLESS STEEL

Dia.	Wire Size	Arbor Hole	Face Width	Trim Length	Max. AH Avail.	Thickness at Face Plates	Max. RPM	Std. Pack	ltem Number
3"	.006	1/2"-3/8"	7/16"	1/2"	3/4"	7/16"	12,500	2	00244
	.0118								00264
4"	.006	1/2"-3/8"	1/2"	7/8"	3/4"	7/16"	12,500	2	00154
	.006	5/8"-11 UNC			_	_	14,000	5	00156
	.0118	1/2"-3/8"			3/4"	7/16″	12,500	2	00184
	.014	5/8"-11 UNC			-		14,000	5	13085
6"	.006	5/8"-1/2"	3/4"	1-7/16"	1-1/4"	7/16"	6,000	2	01675
	.0104								01695
	.0118								01705
8"	.006	5/8"	3/4"	2-1/16"	1-1/4"	1/2"	6,000	2	01775
	.0104								01795
	.0118								01805
8"	.0118	1-1/4"★	3/4"	2-1/16"	1-1/4"	1/2"	6,000	2	01809
10"	.014	3/4"	3/4"	2-1/2"	2"	5/8"	4,000	2	01898
12"	.006	1-1/4"★	3/4"	2-15/16"	2-1/2"	1/2"	3,000	2	01939
	.0104								01949

★ 5/16" x 5/32" Double Keyway



WOLVERINE[™] CRIMPED WIRE WHEELS / 302 Stainless / Narrow Face / Provide flexible

brushing action and cost-effective performance in general purpose cleaning and deburring applications.

Dia.	Wire Size	Arbor Hole	Face Width		Max. AH Avail.	Max. RPM	Std. Pack	ltem Number
6"	.014	5/8"-1/2"	3/4"	1-1/4"	5/8"	6,000	2	36201

CRIMPED WIRE WHEELS / 302 Stainless / Medium Face / Flexible brushing action and consistent performance for demanding light-duty cleaning and deburring applications; feature a wider face width to cover more area.

Dia.	Wire Size	Arbor Hole	Face Width	Trim Length	Thickness at Face Plates	Max. RPM	Standard Pack	ltem Number
6"	.0104	2"	1"	1-1/8"	15/16"	6,000	1	06440
	.0118							06450
8"	.0118	2"	1"	1-3/8"	1"	4,500	1	06490
10"	.0118	2"♦	1-1/8"	2"	1"	3,600	1	06530

◆ 1/2" x 1/4" Double Keyway

For arbor hole reducing adapters, see Metal Adapter Table below.

CRIMPED WIRE WHEELS / 302 Stainless / Wide Face / Flexible brushing action and consistent

performance for demanding light-duty cleaning and deburring applications; feature a wider face width to cover more area.

Dia.	Wire Size	Arbor Hole	Face Width	Trim Length	Thickness at Face Plates	Max. RPM	Standard Pack	ltem Number
6"	.006	2"	1-1/4"	1-1/8"	1"	6,000	1	03480
	.0118							03510
	.014							03520
8"	.0118	2"	1-1/2"	1-3/8"	1-3/8"	4,500	1	03590
12"	.014	2"	2"	2-7/8"	1-9/16"	3,000	1	03680
For arbor hole redu	cing adapters, see	Metal Adapter Tabl	le below.					

PRODUCT SELECTION TIP


Wire brushes are often the best choice for cleaning welds and surfaces – wire brushes don't remove base material. Choose stainless wire brushes with a twisted knot design for more aggression or a crimped design for more surface area coverage.











17611

Dia.	Wire Size	Arbor Hole	Face Width	Trim Length	Max. RPM	Standard Pack	ltem Number
1"	.003	1/4"	3/16"	1/4"	20,000	10	16461
	.005						16471
1-1/4"	.006	1/4"	1/4"	3/8"	20,000	10	16511
	.008						16521
1-1/2"	.006	3/8"	1/4"	7/16"	20,000	10	16702
	.008			7/16"			16712
2"	.005	1/2"	3/8"	3/4"	20,000	10	16833
	.008						16843
	.0104						16853
	.014	1/2"-3/8"					16873
3"	.006	1/2"-3/8"	5/8"	1"	20,000	10	16933
	.008						16943
	.0118						16963
	.014						16973

CONFLEX BRUSHES / 302 Stainless / 1/4" Stem Flexible brushing action and consistent performance for demanding light-duty cleaning & deburring. Wire Standard Face Trim Max. Width RPM Diameter Size Length Pack .0118 3/8" 1/2" 20,000 10 2" 3" .014 1/2" 1" 20,000 10

CONFLEX BRUSHES / 302 Stainless / Wide Face / 1/4" Stem Flexible brushing action and consistent performance for demanding light-duty cleaning & deburring; feature a wider face width to cover more area.

Diameter	Wire Size	Face Width	Trim Length	Max. RPM	Standard Pack	ltem Number
1-3/4"	.008	1/2"	5/8"	20,000	10	17608
3"	.008	1"	15/16"	20,000	10	17637

17637





Diameter	Wire Size	Face Width	Trim Length	Max. RPM	Standard Pack	ltem Number
1-1/2"	.006	1/4"	3/8"	20,000	10	17971
	.008					17972
	.0118					17973
2"	.008	3/8"	7/16"	20,000	10	17974
	.014					17975
2-1/2"	.008	7/16"	9/16"	20,000	10	17976
	.014					17977
3"	.008	1/2"	13/16"	20,000	10	17978
	.014					17979
4"	.008	9/16"	1-5/16"	15,000	10	17981
	.014					17982



17933



CONCAVE B	RUSHES / 302 Stainless / 1	/4" Stem /	Saucer-shaped radial wheels provide
flexible brushing a	ction for addressing corners and ha	ard-to-reach	areas.

Diameter	Wire Size	Face Width	Trim Length	Max. RPM	Standard Pack	ltem Number
1-1/2"	.006	1/4"	3/8"	20,000	10	17930
	.0118					17931
2"	.014	3/8"	1/2"	20,000	10	17933
2-1/2"	.014	7/16"	5/8"	20,000	10	17935
3"	.006	1/2"	15/16"	20,000	10	17936
	.014					17937

	INIATURE WIRE WHEEL BRUSHES / 302 Stainless e crimped wire fill for light-duty cleaning and deburring.									
Diameter	Wire Size	Trim Length	Stem Size	Stem Length	Max. RPM	Standard Pack	ltem Number			
5/8"	.005	1/8"	1/8"	1-1/2"	37,000	144	99554			
3/4"	.005	3/16"	1/8"	1-1/2"	37,000	144	26005			
1"	.003	5/16"	1/8"	1-1/2"	37,000	144	26014			
	.005						26017			
1-1/2"	.005	1/2"	1/8"	1-1/2"	25,000	144	26294			



ltem

Number

17611

17618





KNOT WIRE CUP BRUSHES / 302 Stainless / Single Row / Heavy-duty brushing action with some flexibility; ideal for demanding cleaning applications on relatively flat surfaces.

Diameter	Wire Size	Arbor Hole	Trim Length	Max. RPM	Standard Pack	ltem Number
2-3/4"	.014	5/8"-11 UNC	1"	14,000	1	13009
2-3/4"	.020	M10 x 1.25	1"	14,000	1	13253
		M10 x 1.50				13254
		M14 x 2.0				13255
		3/8"-24 UNF				13256
		1/2"-13 UNC				13257
		5/8"-11 UNC				13258
3-1/2"	.023	M14 x 2.0	7/8"	13,300	1	13159
		3/8"-24 UNF				13160
		5/8"-11 UNC				13163
4"	.014	5/8"-11 UNC	1-1/4"	10,200	1	12406
	.023					12416
6"	.014	5/8"-11 UNC	1-3/8"	6,600	1	12456
	.023					12476
6"	.023	5/8"-11 UNC	1-5/8"	6.000	1	12886

Items are also available in 316 STAINLESS STEEL: .020 wire only.

WOLVERINE[™] KNOT WIRE CUP BRUSH / 302 Stainless / Single Row

Provide an aggressive brushing action for general-purpose surface cleaning applications.

	Wire	Arbor	Trim	Max.	Standard	Item	
Diameter	Size	Hole	Length	RPM	Pack	Number	_
3"	.020	5/8"-11 UNC	1"	14,000	1	36239	

KNOT WIRE CUP BRUSHES / 302 Stainless / Double Row / Very aggressive brushing while

still maintaining some flexibility; ideal for severe cleaning applications.								
Diameter	Wire Size	Arbor Hole	Trim Length	Max. RPM	Standard Pack	ltem Number		
4"	.020	5/8"-11 UNC	1-1/4"	9,000	1	12726		
6"	.023	5/8"-11 UNC	1-3/8"	6,600	1	12636		

CRIMPED WIRE CUP BRUSHES / 302 Stainless / Very flexible brushing action and consistent	
performance for demanding light-duty cleaning applications; feature a threaded nut for use on angle grinders.	

Diameter	Wire Size	Arbor Hole	Trim Length	Max. RPM	Standard Pack	ltem Number
3-1/2"	.014	M10 x 1.25	7/8"	13,300	1	13182
		M14 x 2.0				13184
		3/8"-24 UNF				13185
		1/2"-13 UNC				13187
		5/8"-11 UNC				13188
4"	.020	5/8"-11 UNC	1-3/8"	10,200	1	14126
5"	.020	5/8"-11 UNC	1-1/4"	9,000	1	14256
6"	.020	5/8"-11 UNC	1-1/4"	6,600	1	14166*
*With internal nut						

With internal nut

UTILITY CRIMPED WIRE CUP BRUSHES / 302 Stainless / Provide flexible brushing action and consistent performance for light-duty cleaning applications; featuring a 1/4" stem for use on air tools.

Diameter	Wire Size	Trim Length	Overall Length	Max. RPM	Standard Pack	ltem Number
1-3/4"	.006	3/4"	2-5/16"	13,000	10	14303
	.0118					14304
2"	.008	5/8"	2-7/8"	13,000	10	14318
	.0118					14319
2-1/2"	.008	7/8"	3-1/8"	13,000	10	14320
	.014					14321

MINIATURE WIRE CUP BRUSH / 302 Stainless

Fine crimped wire fill for light-duty cleaning or deburring in confined areas.

the entropy the finite add of a country in control a court									
Diameter	Wire Size	Trim Length	Stem Size	Stem Length	Overall Length	Max. RPM	Standard Pack	ltem Number	
5/8"	.005	1/4"	1/8"	1-1/2"	2"	37,000	144	26076	



e













Cleaning a weld join with a controlled flare end brush.















Diameter	Wire Size	Trim Length	Overall Length	Max. RPM	Standard Pack	ltem Number
1/2"	.006	1-1/8"	2-7/8"	20,000	10	10215
	.0104					10216
	.014					10218
3/4"	.006	1-1/8"	2-7/8"	20,000	10	10220
	.0104					10211
	.014	7/8"	2-5/8"	22,000		10029
	.020					10030
1-1/8"	.006	1-1/8"	2-9/16"	20,000	10	10142 •
	.0104		2-7/8"			10213
	.014	7/8"	2-5/8"	22,000		10031
	.020					10032
D BLACK ITEM nu	mbers indicate color-co	ded brushes for easy ider	ntification.			 Coated

KNOT WIRE END BRUSHES / 302 Stainless / Hollow End / Nickel-plated Cup Compliant With DOD MIL STD 2041D(SH) / Heavy-duty brushing action with some flexibility; ideal for more demanding cleaning applications in recessed areas



	Wire	Trim	Overall	Max.	Standard	ltem			
Diameter	Size	Length	Length	RPM	Pack	Number			
3/4"	.014	7/8"	2-5/8"	22,000	10	10387			
	.020					10388			
1-1/8"	.014	7/8"	2-5/8"	22,000	10	10392			
	.020					10393			

WOLVERINE[™] KNOT WIRE END BRUSHES / 302 Stainless / Hollow End

Heavy-duty brushing action; Engineered to provide cost-effective use for less demanding applications.

-	. 1		17
		Ē	
	1		

Diameter	Wire Size	Trim Length	Overall Length	Max. RPM	Standard Pack	ltem Number
3/4"	.014	7/8"	2-5/8"	22,000	10	36287
1"	.014	7/8"	2-5/8"	22,000	10	36289

CRIMPED WIRE END BRUSHES / 302 Stainless / Solid End / Very flexible brushing action ideal for more demanding light-duty cleaning applications in corners and hard-to-reach areas.



Diameter	Wire Size	Trim Length	Overall Length	Max. RPM	Standard Pack	ltem Number
1/2"	.006	7/8"	2-9/16"	25,000	10	10013
	.0104					10014
	.014					10015
	.020					10016
3/4"	.006	7/8"	2-9/16"	22,000	10	10017
	.0104					10018
	.014					10019
	.020					10020
1"	.006	1"	2-3/16"	22,000	10	10021
	.0104					10022
	.014					10023
	.020	1-1/8"	2-15/16"			10024

BOLD BLACK ITEM numbers indicate color-coded brushes for easy identification.

CRIMPED WIRE END BRUSHES / 302 Stainless / Coated Cup / Very flexible brushing action ideal for more demanding light-duty cleaning applications in corners and hard-to-reach areas. The plastic sleeve covering the cup protects the work surface from being scratched or marked.



Diameter	Wire Size	Trim Length	Overall Length	Max. RPM	Standard Pack	ltem Number
1/2"	.006	7/8"	2-9/16"	25,000	10	11010
	.0104					11011
3/4"	.006	7/8"	2-9/16"	22,000	10	11013
	.0104					11014
1"	.006	7/8"	2-3/4"	22,000	10	11016
	.0104	1"				11017



WOLVERINE CRIMPED WIRE END BRUSHES / 302 Stainless / Solid End

Flexible brushing action and engineered to provide cost-effective use for less demanding applications

Diameter	Wire Size	Trim Length	Overall Length	Max. RPM	Standard Pack	ltem Number
3/4"	.006	7/8"	2-9/16"	22,000	10	36283
1"	.006	7/8"	2-3/4"	22,000	10	36285

Diameter	Wire Size	Trim Length	Overall Length	Max. RPM	Standard Pack	ltem Number
1/2"	.006	7/8"	2-9/16"	25,000	10	10370
	.0104					10371
	.014					10372
	.020					10373
3/4"	.006	7/8"	2-9/16"	22,000	10	10374
	.0104					10375
	.014					10376
	.020					10377
1"	.006	1"	2-7/8"	22,000	10	10378
	.0104					10379
	.014					10380
	.020	1-1/8"	2-15/16"			10381

CRIMPED WIRE END BRUSHES / 302 Stainless / Banded / Bands around the fill reduce the exposed trim length and limit brush flaring at operating speed to provide an aggressive, controlled brushing action.

Diameter	Wire Size	Trim Length*	Overall Length	Max. RPM	Standard Pack	Item Number
1/2"	.006	9/16"	2-9/16"	20,000	10	11110
3/4"	.006	7/16"	2-11/16"	20,000	10	11112
	.0104	3/8"				11113
1"	.006	3/8"	2-5/8"	13,000	10	11114
	.0104					11115

*Trim length from bands

*CONTROLLED FLARE END BRUSHES / 302 Stainless / Feature uniquely trimmed crimped wire fill for more effective brushing action and greatly enhanced durability when cleaning corners and fillet welds.

Diameter	Wire Size	Trim Length	Overall Length	Max. RPM	Standard Pack	ltem Number
1/2"	.0104	7/8"	2-9/16"	25,000	10	10313
	.014					10314
	.020					10315
3/4"	.0104	7/8"	2-9/16"	22,000	10	10317
	.020					10319
1"	.0104	1"	2-7/8"	22,000	10	10321
	.014					10322
1"	.020	1-1/8"	2-15/16"	22,000	10	10323

*Patent #8,186,000 B2

CRIMPED WIRE PILOT BONDING BRUSHES / 302 Stainless / Solid End / Banded Designed to clean around rivet holes in aluminum aircraft panels but may be used in similar applications.

Diameter	Wire Size	Trim Length	Overall Length	Pilot Diameter	Max. RPM	Standard Pack	ltem Number
1/2"	.005	3/8"	2-1/4"	3/32"	20,000	10	10056
				1/8"			10057
				5/32"			10058
				3/16"			10059

POLYFLEX⁻ ENCAPSULATED CRIMPED WIRE END BRUSHES

302 Stainless / Standard Duty / Feature fill material that has been encapsulated in an elastomer that gradually wears away to keep only the wire tips exposed; ideal for applications that require maximum aggression and no flaring.

Diameter	Wire Size	Trim Length	Overall Length	Max. RPM	Standard Pack	ltem Number
1/2"	.0104	7/8"	2-9/16"	18,000	10	35500
3/4"	.0104	7/8"	2-9/16"	16,000	10	35505

CIRCULAR FLARED END BRUSHES / 302 Stainless / Crimped wire has been "pre-flared" to match the working angle of the brush at operating speed; for broad and slightly contoured surfaces.

	Wire	Max.	Standard	ltem
Diameter	Size	RPM	Pack	Number
1"	.006	25,000	1	10042
	.008			10043
1-1/2"	.006	20,000	1	10045
	.008			10046
	.020			10047
2-3/4"	.008	16,000	2	10048
3"	.006	16,000	2	10151
	.008			10050
	.020			10074
4"	.008	15,000	1	96705



Cleaning around rivet holes with a pilot bonding brush.



















MINIATURE WIRE END BRUSHES / 302 Stainless

Fine crimped wire fill for light-duty cleaning or deburring in very small recessed areas or IDs.

Dia.	Wire Size	Trim Length	Stem Size	Stem Length	Overall Length	Max. RPM	Standard Pack	ltem Number
3/16"	.003	1/4"	1/8"	1-1/4"	1-7/8"	37,000	144	26099
1/4"	.005	7/16"	1/8"	1-1/4"	2-1/8"	37,000	144	26108
5/16"	005	9/16"	1/8"	1-1/4"	2-3/8"	25 000	144	26114

DOUBLE STEM, DOUBLE SPIRAL / 302 Stainless / Feature four stem wires and a double



26114

Diameter	Wire Size	Brush Part	Stem Diameter	Overall Length	Max. RPM	Standard Pack	ltem Number
1/2"	.004	2"	5/32"	5"	2,000	10	21116
.00	.006						21117
	.005	2"	7/32"	5"	2,000	10	21118
	.008						21119
3/4" .0	.006	2-1/2"	1/4"	5-1/2"	2,000	10	21120
	.0104						21121
7/8"	.006	2-1/2"	1/4"	5-1/2"	2,000	10	21122
	.0104						21123
1"	.006	2-1/2"	1/4"	5-1/2"	2,000	10	21124
	.0104						21125
1-1/4"	.006	2-1/2"	1/4"	5-1/2"	2,000	10	21245
	.0104						21236
1-1/2"	.014	2-1/2"	1/4"	5-1/2"	2,000	10	21413

ROUND / 302 Stainless / Feature a single continuous length of stainless stem wire and a single spiral of crimped wire for flexible brushing action; for use on smooth or threaded blind holes.

		0 ,					
Diameter	Wire Size	Brush Part	Stem Diameter	Overall Length	Max. RPM	Standard Pack	ltem Number
1/4"	.004	1"	1/8"	3-1/2"	2,000	10	21081
3/8"	.004	1"	1/8"	3-1/2"	2,000	10	21082
	.008						21240
7/16"	.005	1"	1/8"	3-1/2"	2,000	10	21181
1/2"	.005	1"	3/16"	3-1/2"	2,000	10	21083
9/16"	.0104	1"	3/16"	3-1/2"	2,000	10	21404
5/8"	.005	1"	3/16"	3-1/2"	2,000	10	21084
3/4"	.006	1"	7/32"	3-1/2"	2,000	10	21085
7/8"	.006	1"	7/32"	3-1/2"	2,000	10	21086
1"	.005	1"	1/4"	3-1/2"	2,000	10	21340
	.008	1					21087
1-1/8"	.008	1"	1/4"	3-1/2"	2,000	10	21088
1-1/4"	.008	1"	1/4"	3-1/2"	2,000	10	21089

BURRITE / 302 Stainless / Feature a single continuous length of stainless stem wire filled with a tuft of crimped wire to provide an aggressive flat side action; ideal for cleaning and deburring internal threads.

Diameter	Wire Size	Brush Part	Stem Diameter	Overall Length	Max. RPM	Standard Pack	ltem Number
1/4"	.005	9/16"	3/32"	2-1/8"	2,000	10	21050
3/8"	.005	9/16"	3/32"	2-1/8"	2,000	10	21051
1/2"	.005	9/16"	3/32"	2-1/8"	2,000	10	21053
5/8"	.005	5/8"	1/8"	2-1/4"	2,000	10	21055
3/4"	.005	5/8"	1/8"	2-1/4"	2,000	10	21056
7/8"	.005	5/8"	1/8"	2-1/4"	2,000	10	21057
1"	.005	5/8"	1/8"	2-1/4"	2,000	10	21058

SINGLE STEM, SINGLE SPIRAL / 302 Stainless / A single continuous length of galvanized steel stem wire with a formed eye loop for convenient hand use. The single spiral of straight wire fill allows for easy manual insertion into the ID.

Diameter	Wire Size	Brush Part	Stem Diameter	Overall Length	Standard Pack	ltem Number
1/8"	.003	1"	3/32"	6"	10	21249
3/16"	.003	1-1/2"	3/32"	7"	10	21098
	.005					21099
1/4"	.003	1-1/2"	3/32"	7"	10	21100
	.005					21101
3/8"	.004	2"	1/8"	8"	10	21414
	.006					21103
1/2"	.004	2"	1/8"	8"	10	21104
	.006					21105





21095

1 de de de de de

CURVED HANDLE SCRATCH BRUSHES / 302 Stainless / .012 Wire Size / Hardwood Block

Block Size	Brush Length	Number of Rows	Trim Length	Standard Pack	ltem Number
13-3/4" x 1-1/8"	5-1/4"	3 x 14	1-1/4"	12	44432*
14" x 7/8"	5-1/2"	3 x 19	1-3/16"	12	44054
14" x 1-1/8"	6"	4 x 18	1-3/16"	12	44057

Cleaning a weld with a small scratch brush.

Items are also available in 316 STAINLESS STEEL

VORTEC PRO* CURVED HANDLE SCRATCH BRUSHES / 302 Stainless / .012 Wire Size / Hardwood block / Reliable and efficient brushes at a value price.

Block Size	Brush Length	Number of Rows	Trim Length	Standard Pack	ltem Number
13-1/2" x 1"	6"	3 x 19	1"	12	25154
14" x 1-1/8"	6"	4 x 18	1"	12	25202

SHOE HANDLE SCRATCH BRUSHES / 302 Stainless / .012 Wire Size / Hardwood Block

Ideal for cleaning and prepping surfaces.

Block Size	Brush Length	Number of Rows	Trim Length	Standard Pack	ltem Number
10" x 3/8"	5"	1 x 17	1-1/16"	12	44101
10" x 3/8"	5"	1 x 17	3/4"	12	44235
10" x 5/8"	5"	2 x 17	1-3/16"	12	44062
10" x 1-1/8"	5"	4 x 16	1-3/16"	12	44064
11"	5"	4 x 16	1-3/16"	12	44299 •

Plastic block



Block	Brush	Number	Trim	Standard	ltem
Size	Length	of Rows	Length	Pack	Number
10" x 1"	5"	4 x 16	1"	12	25104

SMALL HAND SCRATCH BRUSHES / 302 Stainless

Ideal for cleaning and prepping surfaces.

Block Size	Block	Number of Rows	Wire Size	Trim Length	Standard Pack	ltem Number
		S	tainless Steel Wir	8		
7-1/2" x 1/2"	Plastic	3 x 7	.006	1/2"	36	44075
7-1/2" x 1/2"	Wood	3 x 7	.006	1/2"	36	44167
7-3/4" x 3/8"	Wood	3 x 7	.006	1/2"	36	44551 *
8-3/4" x 1/2"	Wood	2 x 9	.006	5/8"	36	95013
, Wire drawn						
				It	ems are also available in 31	6 STAINI ESS STEFI
				It	ems are also available in 31	I6 STAINLESS STEE



25104

25154

.

VORTEC PRO SMALL HAND SCRATCH BRUSHES / 302 Stainless

Reliable and efficient brushes at a value price.

Block Size	Handle	Number of Rows	Trim Length	Standard Pack	ltem Number
7-1/2" x 1/2"	Wood	3 x 7	1/2"	36	44805
7-1/2" x 1/2"	Plastic	3 x 7	1/2"	36	44806



THE WEILER PROMISE

At Weiler, we passionately embrace change to improve our products and our processes to move the company and our customers forward. By bringing new ideas and creative problem solving together in an open, collaborative environment, we will improve our customers' productivity and create profitable growth.



For the full offering of Weiler products, please refer to our Full Line Catalog or visit our website. To discuss specific requirements with a product specialist call our applications hotline at 888.299.2777.

Weiler Abrasives Group One Weiler Drive Cresco, PA 18326 USA

WC456 / 8202NP / ©2023 Weiler Abrasives Group. All Rights Reserved.



800.835.9999 / weilerabrasives.com

